

AC184 Series

Multipurpose Accelerometer, Side Exit 2 Pin Connector, M8x1.25 Captive Bolt, 100 mV/g, $\pm 10\%$



Product Features

Perfect for M8 Mounting Applications


High Performance in a Low-Cost Sensor

- ▶ 100 mV/g Sensitivity, $\pm 10\%$
- ▶ ± 80 g, peak Dynamic Range
- ▶ Standard 2 Pin MIL Connection or Integral Cable

AC184-1A

2 Pin Connector

Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common




Stock Product

AC184-2C & -7A

2C = CB103 Integral Cable
7A = CB124 Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC184-3C

CB206 Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC184-6C

CB611 Heavy Duty Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC184-6N

CB111 FEP Jacketed Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Sensitivity ($\pm 10\%$)	100 mV/g		Environmental		
Frequency Response (± 3 dB)	30-600,000 CPM	0.5-10000 Hz	Operating Temperature Range	-58 to 250 °F	-50 to 121 °C
Dynamic Range	± 80 g, peak *Vsource ≥ 22 V, 12Vbias		Maximum Shock Protection	5,000 g, peak	
Transverse Sensitivity	$\leq 5\%$		Electromagnetic Sensitivity	CE	
Electrical			Sealing	Welded, Hermetic	
Settling Time	<2.5 seconds		Submersible Depth	200 ft.	60 m
Voltage Source	18-30 VDC		SIL Rating	SIL 2	
Constant Current Excitation	2-10 mA		Physical		
Spectral Noise @ 10 Hz	14 μ g/ $\sqrt{\text{Hz}}$		Sensing Element	PZT Ceramic	
Spectral Noise @ 100 Hz	2.3 μ g/ $\sqrt{\text{Hz}}$		Sensing Structure	Shear Mode	
Spectral Noise @ 1000 Hz	2 μ g/ $\sqrt{\text{Hz}}$		Weight	6 oz	170 grams
Output Impedance	<100 ohm		Case Material	316L Stainless Steel	
Bias Output Voltage	10-14 VDC		Mounting Thread	M8x1.25	
Case Isolation	>10 ⁸ ohm		Connector (Non-Integral)	2 Pin MIL-C-5015	
			Resonant Frequency	1,200,000 CPM	20000 Hz
			Mounting Torque	2 to 5 ft. lbs.	2.7 to 6.8 Nm
			Mounting Hardware Supplied	M8x1.25 Captive Bolt	
			Calibration Certificate	CA10	

Typical Frequency Response

