

AC298 Series

Premium, Compact Multipurpose Accelerometer, Side Exit 2 Pin Connector,
M8x1.25 Captive Bolt, 100 mV/g, $\pm 5\%$



VIBRATION ANALYSIS HARDWARE



Product Features


Premium Performance in a Compact, Side-Exit Sensor
Very Low Noise and Superior RF Immunity

- ▶ 100 mV/g Sensitivity, $\pm 5\%$
- ▶ $\pm 80g$ Dynamic Range
- ▶ Standard 2 Pin MIL Connection on Non-Integral Option

AC298-1D

2 Pin Connector

Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common




Stock Product

AC298-2D & -7A

2D = CB103 Integral Cable
7A = CB124 Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC298-3D

CB206 Armored Integral cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC298-6D

CB611 Heavy Duty Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC298-6N

CB111 Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Sensitivity ($\pm 5\%$)	100 mV/g		Environmental		
Frequency Response ($\pm 3dB$)	30-480,000 CPM	0.5-8000 Hz	Operating Temperature Range	-58 to 250 °F	-50 to 121 °C
Frequency Response ($\pm 10\%$)	60-150,000 CPM	1,0-2500 Hz	Maximum Shock Protection	5,000 g, peak	
Frequency Response ($\pm 5\%$)	600-120,000 CPM	10-2000 Hz	Electromagnetic Sensitivity	CE	
Dynamic Range	$\pm 80 g$, peak *Vsource $\geq 22V$, 12Vbias		Sealing	Welded, Hermetic	
Transverse Sensitivity	$\leq 5\%$		Submersible Depth	200 ft.	60 m
Electrical			SIL Rating	SIL 2	
Settling Time	<2 Seconds		Physical		
Voltage Source	18-30 VDC		Sensing Element	PZT Ceramic	
Constant Current Excitation	2-10 mA		Sensing Structure	Shear Mode	
Spectral Noise @ 10 Hz	8 $\mu g/\sqrt{Hz}$		Weight	3.4 oz	96 grams
Spectral Noise @ 100 Hz	4 $\mu g/\sqrt{Hz}$		Case Material	316L Stainless Steel	
Spectral Noise @ 1000 Hz	2 $\mu g/\sqrt{Hz}$		Connector (Non-Integral)	2 Pin MIL-C-5015	
Output Impedance	<100 ohm		Resonant Frequency	1,380,000 CPM	23000 Hz
Bias Output Voltage	10-14 VDC		Mounting Torque	2 to 5 ft. lbs.	2.7 to 6.8 Nm
Case Isolation	>10 ⁸ ohm		Mounting Hardware Supplied	M8x1.25 Captive Bolt	
			Calibration Certificate	CA10	

Typical Frequency Response

