

LP364 Series

Dual Output Loop Power Sensor, 4-20 mA Output Proportional to Vibration in Acceleration with °C Temperature Output, Side Exit 3 Pin Connector



Product Features


4-20 mA Current Proportional to Vibration in Acceleration

- ▶ Peak and RMS Outputs Available
- ▶ Transmits Signals Over Long Distances with No Signal Loss
- ▶ Outputs to PLC, DCS, SCADA

LP364-XXX-1E

3 Pin Connector

Connector	Polarity
A	(+) Loop Power
B	(-) Loop Power Return
C	(+) Temperature Voltage




Built To Order

LP364-XXX-2E

CB105 Molded Integral Cable

Conductor	Polarity
Red	(+) Loop Power
Black	(-) Loop Power Return
White	(+) Temperature Voltage
Shield	Cable Drain Wire




Built To Order

LP364-XXX-3E

CB218 Armored Integral Cable

Conductor	Polarity
Red	(+) Loop Power
Black	(-) Loop Power Return
White	(+) Temperature Voltage
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	LP364	M/LP364	Physical		
Temperature Output	10 mV/°C		Sensing Element	PZT Ceramic	
	within the range -20 to 100°C		Sensing Structure	Shear Mode	
Tolerance: 4 mA	(± 10%)		Weight	4.9 oz	140 grams
Tolerance: 20 mA	(± 10%)		Case Material	316L Stainless Steel	
Tolerance: Temperature	(± 5°C)		Mounting Thread	1/4-28	
Electrical			Connector (Non-Integral)	3 Pin MIL-C-5015	
Settling Time	<30 Seconds		Mounting Torque	2 to 5 ft. lbs.	2.7 to 6.8 Nm
Voltage Source	15-30 VDC		Mounting Hardware Supplied	1/4-28 Captive Bolt	M6x1 Captive Bolt
Case Isolation	>10 ⁸ ohm		Calibration Certificate	Current Output @ 100 Hz	
Environmental					
Operating Temperature Range	-4 to 212°F	-20 to 100°C			
Electromagnetic Sensitivity	CE				
Sealing	Welded, Hermetic				
Submersible Depth	200 ft.	60 m			

Ordering Information

/LP364 -						/		/					
Bolt Type		Measurement Range		Type		Frequency Range ±3dB		Style		Armor Length (Integral)		Cable Length (Integral)	
Blank = ¼-28 M = M6x1		0 = 0-1 g 2 = 0-2 g 5 = 0-5 g 10 = 0-10 g 20 = 0-20 g		P = Peak R = RMS		1 = 600-60000 CPM (10-1000 Hz) 2 = 180-150000 CPM (3-2500 Hz) 3 = 180-60000 CPM (3-1000 Hz) 4 = 180-300000 CPM (3-5000 Hz) 5 = 180-600000 CPM (3-10000 Hz)		1E = 3 Pin MIL C-5015 2E = Integral Cable 3E = Armor Jacket		010 = 10 ft/3 m 020 = 20 ft/6 m 030 = 30 ft/9 m 050 = 50 ft/15 m 100 = 100 ft/30 m		010 = 10 ft/3 m 020 = 20 ft/6 m 030 = 30 ft/9 m 050 = 50 ft/15 m 100 = 100 ft/30 m	
*Custom Lengths Available Upon Request													