

LP383-M12A Series

Dual Output Loop Power Sensor, 4-20 mA Output Proportional to Vibration in Acceleration with RTD Temperature Output, Side Exit 4 Pin M12 Connector




Product Features

Dual Output with 4-20 mA Current Proportional to Vibration in Velocity and PT100 Sensor for RTD Temperature Output

View [2 Wire vs. 4 Wire RTD Systems Explained](#)

- ▶ Compatible with CTC M4TR4 (Polycarbonate), M4RTR4 (PPS) and MV4R4 (Viton Boot) Connectors for 4 Wire RTD Systems
- ▶ Compatible with CTC M4TR2 (Polycarbonate), M4RTR2 (PPS), and MV4R2 (Viton Boot) Connectors for 2 Wire RTD Systems



Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	LP383-M12A	M/LP383-M12A	Physical		
Temperature Measurement Range	-4 to 212 °F	-20 to 100 °C	Sensing Element		PZT Ceramic
Temperature Sensor	PT100 RTD		Sensing Structure		Shear Mode
Tolerance: 4 mA	(± 10%)		Weight	4.7 oz	132 grams
Tolerance: 20 mA	(± 10%)		Case Material		316L Stainless Steel
Electrical			Mounting Thread		1/4-28
Settling Time	<30 Seconds		Connector (Non-Integral)		4 Pin M12
Voltage Source	15-30 VDC		Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
Case Isolation	>10 ⁸ ohm		Mounting Hardware Supplied	1/4-28 Captive Bolt	M6x1 Captive Bolt
Environmental			Calibration Certificate		Current Output @ 100 Hz
Operating Temperature Range	-4 to 212 °F	-20 to 100 °C			
Electromagnetic Sensitivity	CE				
Sealing	Welded, Hermetic				

Ordering Information

/LP383 -	Stud Type Blank = ¼-28 M = M6x1 M8 = M8x1.25	Measurement Range 0 = 0-1 g 2 = 0-2 g 5 = 0-5 g 10 = 0-10 g 20 = 0-20 g	Type P = Peak R = RMS	Frequency Range ±3dB 1 = 600-60000 CPM (10-1000 Hz) 2 = 180-150000 CPM (3-2500 Hz) 3 = 180-60000 CPM (3-1000 Hz) 4 = 180-300000 CPM (3-5000 Hz) 5 = 180-600000 CPM (3-10000 Hz)	Style M12A = 4 Pin M12
---	--	---	--	---	--------------------------------------