

CAN BUS AND CAN FD INTERFACES



DEWESoft 7-YEAR WARRANTY

Our warranty covers that the instruments function as promised for a period of 7 years from the day of the delivery.



CAN FD, XCP, FLEXRAY AND LIN

Using third party hardware, additional interfaces are supported.

RAW DATA ANALYZER

Graphical interface for easy CAN decoding and finding signals without a CAN DBC.

OBDII AND J1939 SUPPORT

CAN interfaces have XCP/CCP, OBDII, J1939 and other standard support.

Multichannel USB and single channel EtherCAT® CAN BUS. Software with support for OBDII, J1939, XCP/CCP, CAN transmit, DBC and AUTOSAR XML files.

NATIVE CAN FD SUPPORT

SIRIUS can be ordered with CAN FD or with standard CAN port.

PLUG-AND-PLAY CAN INTERFACES

Robust and easy to use interfaces. Connect your CAN device to the USB port of any laptop or PC, or to any SBOX or KRYPTON CPU computer. The device will be recognized automatically, and be ready to use in a moment.

1, 2, 4 OR 9 CAN PORTS

Multiple CAN devices can be connected together to expand to more CAN ports.

DBC AND ARXML FILE SUPPORT

Included DewesoftX software enables import of DBC or AUTOSAR XML files which will automatically set the CAN channel list.

FANLESS CHASSIS AVAILABLE

1, 2 and 4 port CAN port are fanless by default, and even the 9 port CAN device can also be built into a fanless aluminium chassis with IP50 degree of protection for worry-free CAN acquisition in harsh, dusty environments.