

KRYPTON® RUGGED SYSTEMS

KRYPTON® CPU

Compact, highly portable logger for data recording in harsh environments from -40 to +70 °C operating range.



KRYPTON®

Ultra rugged and distributable data acquisition devices from -40 to +85 °C operating range.



KRYPTON® 1 SERIES

Distribute your measurements down to a single channel.



MADE TO BE EXTREME

IP67, dust proof, waterproof, 100 g shock and vibration resistant, wide temperature operating range.

Rugged DAQ system that can be distributed down to a single channel and placed close to sensors. All DAQ systems offer IP67 degree of protection and are thus waterproof, dustproof, shock resistant up to 100 g, and can withstand a temperature range up to -40 °C to 85 °C.

SINGLE CABLE

With up to 100 m between devices for power, data and synchronization.

DISTRIBUTABLE DEVICES

Locate your data acquisition hardware close to the sensors.

KRYPTON® WATERPROOF



UP TO 100 m BETWEEN UNITS

KRYPTON units can be distributed over the large area with distances of up to 100 meters (328 feet) between DAQ nodes.

DISTRIBUTED DAQ

Distributed measurement hardware that can be located close to sensors. Compared to traditional DAQ systems, this has many advantages such as shorter cable runs and less potential for signal noise. KRYPTON systems can be distributed down to a single channel.

EtherCAT® DAQ

Protocol with 100Mb/s bus speed is used for data transmission, data synchronization, and power supply. KRYPTONs are connected with a single cable for data, power, and sync.

RUGGED IP67

These modules are built with tough-as-nails IP67 protection - they're ready to go to work in extreme weather and under the harshest conditions.

Rugged and distributable data acquisition modules. EtherCAT® interface for analog and digital I/O and IP67 degree of protection.

UP TO 20 kS/s/CH SAMPLING RATE

Most KRYPTON channels in the EtherCAT® line can achieve sampling rates up to 20 kS/s.

FROM 3 TO 16 CHANNEL UNITS

Modules are available from a 3 channel unit, ranging up to larger 8 and 16 channel modules.

KRYPTON® WATERPROOF SPECS

	STG	TH	TH-HS	RTD	ACC	LV	LA	DIO	CNT
Connectors	DB9, L2B10f	Thermocouple	Thermocouple	L0B6f	BNC	BNC	BNC	DB25	L1T7f
#ch per module	3x, 6x	8x, 16x	8x, 16x	8x	4x, 8x	4x, 8x	8x	16xDI, 16xDO 8xDI, 8xDO	4xCNT
Data rate / channel	20 kS/s	100 S/s	100 S/s, upgradable to 10 kS/s	100 S/s	20 kS/s	20 kS/s	20 kS/s	40 kS/s	20 kS/s
Resolution	24-bit	24-bit	24-bit	24-bit	24-bit	24-bit	24-bit	digital	100 MHz timebase 5 ppm, 20 ppm max
Bandwidth	0.49*fs	X	0.49*fs (max. 1 kHz)	X	0.49*fs	0.49*fs	0.49*fs	X	10 MHz
Voltage ranges	±10 V, ±1 V, ±100 mV, ±10 mV	±1 V, ±100 mV	±1 V, ±100 mV	±1 V, ±100 mV	±10 V, ±5 V, ±1 V, ±200 mV	±50 V	±20 mA	CMOS compatible	TTL (Low: <0.8 V, High > 2 V)
Input coupling	DC	DC	DC	DC	DC, AC 0.1 Hz, 1 Hz	DC	DC	DC	
Sensor excitation	0...15 V max. 0.4 W/ch (45 mA limit)	X	X	X	IEPE 4 mA, 8 mA	-	-	5 V / 300 mA, 12 V / 120 mA, Vsupply / 200 mA*	5 V / 100 mA 12 V / 50 mA
Bridge connection	Full, ½, ¼ 350 Ω, ¼ 120 Ω 3 wire	X	X	X	X	X	X	X	X
Programmable shunt	100 kΩ	X	X	X	X	X	X	X	X
IEPE input	DSI-ACC	X	X	X	✓	X	X	X	X
Resistance	X	X	X	10 kΩ	X	X	X	X	X
Temperature (PTx)	DSI-RTD	X	X	PT100, 200, 500, 1000, 2000	X	X	X	X	X
Thermocouple	DSI-TH	K, J, T, R, S, N, E, C, B	K, J, T, R, S, N, E, C, B	X	X	X	X	X	X
Current	ext. shunt DSI-20mA, DSI-5A	X	X	X	ext. shunt	X	X	X	X
Potentiometer	✓	X	X	X	X	X	X	X	X
LVDT	DSI-LVDT	X	X	X	X	X	X	X	X
Charge	DSI-CHG	X	X	X	X	X	X	X	X
TEDS	✓	X	X	X	✓	X	X	X	X
Isolation voltage	Differential	1000 V	1000 V	1000 V	Differential	1000 V	1000 V	250 V	X
Isolation arrangement	None	Ch-Ch & Ch-GND	Ch-Ch & Ch-GND	Ch-Ch & Ch-GND	None	Ch-Ch & Ch-GND	Ch-Ch & Ch-GND	Isolated common GND	Isolated common GND
Power consumption per module	2.4 W (4 W 120 Ω @ 5 V load) 3xSTG; 5.9 W (8.9 W 120 Ω @ 5 V load) 6xSTG	2.5 W (8xTH) 4 W (16xTH)	2.6 W (8xTH-HS) 4.3 W (16xTH-HS)	2.5 W	4.6 W	3.5 W (4xLV) 6.7 W (8xLV)	6.8 W	2 W	2.3W
Advanced functions	Supports all strain types, TEDS support	High isolation, support of main TC types	High isolation, support of main TC types	X	TEDS support	High isolation, high input range	High isolation, 4-20 mA current loop	X	SuperCounter®

AMPLIFIER SPECS

3xSTG, 6xSTG	Differential universal and strain module
8xTH, 16xTH, 8xTH-HS, 16xTH-HS	Isolated universal thermocouples module
8xRTD	Isolated module for measurements with resistance temperature detectors
4xACC, 8xACC	IEPE accelerometer amplifier
4xLV, 8xLV	Isolated voltage input module

8xLA	Isolated low current amplifier
16xDI, 16xDO, 8xDI-8xDO	Isolated digital input/output module
GPS JUNCTION	Module for synchronization between SIRIUS or KRYPTON EtherCAT® devices to SIRIUS USB device, IRIG-B-DC or GPS
Sync junction	Module used to inject IRIG-B-DC sync signal from USB device to EtherCAT® line
KRYPTON CPU	Rugged data logger