




REVISIONS					
REV.	ECN	DESCRIPTION	BY/DATE	CHK	APPR
A	16546	INITIAL RELEASE	AS 01/24/22	DV	AM

VARIATION TABLE

MODEL	SENSITIVITY	TEDS	OPERATING TEMPERATURE (°F)
3056C	15 pC/g	NO	-60 TO +375
3056F2	5 mV/g	NO	-67 TO +325
3056F3	10 mV/g	NO	-67 TO +325
3056F4	20 mV/g	NO	-67 TO +325
3056F5	50 mV/g	NO	-67 TO +325
3056F6	100 mV/g	NO	-67 TO +325
3056F7	200 mV/g	NO	-67 TO +325
3056F8	500 mV/g	NO	-67 TO +325
3056F2T	5 mV/g	YES	-67 TO +325
3056F3T	10 mV/g	YES	-67 TO +325
3056F4T	20 mV/g	YES	-67 TO +325
3056F5T	50 mV/g	YES	-67 TO +325
3056F6T	100 mV/g	YES	-67 TO +325
3056F7T	200 mV/g	YES	-67 TO +325
3056F8T	500 mV/g	YES	-67 TO +325



SECTION A-A
 180.00°

MOUNTING RECOMMENDATION:
PREPARE A .55 [14] X .55 [14] MIN SURFACE,
FLAT TO .001 TIR.
TAP 10-32 UNF-2B ▽.15 [3.8] MIN.
MOUNTING TORQUE: 10-12 Lb-in.

- 6. TEDS OPERATING TEMPERATURE: -40°F TO +185°F [-40°C TO +85°C]
 - 5. MATES WITH DYTRAN 6010AXX OR 6011AXX CABLE (XX = LENGTH IN FEET).
 - 4. WEIGHT: 10 GRAMS, MAX
 - 3. ARROW INDICATES ACCELERATION DIRECTION FOR POSITIVE OUTPUT.
 - 2. ARROW INDICATES ACCELERATION DIRECTION FOR NEGATIVE OUTPUT.
 - 1. MATERIAL: TITANIUM ALLOY
- NOTES: UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED:
INTERPRET DIM & TOL PER
ASME Y14.5M - 1994.
REMOVE BURRS.
COUNTERSINK INTERNAL THDS
90° TO MAJOR DIA.
CHAM EXT THDS 45° TO MINOR DIA.
THD LENGTHS AND DEPTHS ARE FOR
MIN FULL THDS.
DIMENSIONS APPLY AFTER FINISHING

ALL MACHINED SURFACES. ✓
TOTAL RUNOUT WITHIN .005.
BREAK SHARP EDGES .005 TO .010.
MACHINED FILLET RADII .005 TO .015.
WELDING SYMBOLS PER AWS A2.4.
ABBREVIATIONS PER MIL-STD-12.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES. DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS TOLERANCES ARE:		
DECIMALS	METRIC	ANGLES
.XX ±.03	.X ± 0.8	±1°
.XXX ±.010	.XX ±0.25	

APPROVALS		DATE
ORIG	AS	01/24/22
CHK	DV	03/08/22
APP	AM	03/15/22

DO NOT SCALE DRAWING

THIRD ANGLE PROJECTION
USA






DATA **TRAN**
INSTRUMENTS, INC. Chatsworth, CA

TITLE: **OUTLINE/INSTALLATION
DRAWING, 3056 SERIES**

SIZE	CAGE CODE	DWG NO	REV
B	2W033	127-3056	A

SCALE: 3:1	SHEET 1 OF 1
------------	--------------

Model Number 3056F6T		PERFORMANCE SPECIFICATIONS				DOC NO PS3056F6T																																				
		IEPE ACCELEROMETER				REV B, ECN 17467, 06/10/24																																				
		• HIGH TEMPERATURE • IDEAL LOW FREQUENCY RESPONSE • HERMETICALLY SEALED • TEDS FEATURE • BASE ISOLATED				This family also includes: <table><thead><tr><th>Model</th><th>Sensitivity (mV/g)</th><th>Frequency Response, ±10% (Hz)</th><th>Time Constant (Sec)</th><th>Operating Temp (°F)</th></tr></thead><tbody><tr><td>3056F2T</td><td>5</td><td>1 to 10,000</td><td>0.5 to 1.5</td><td>-67 to +325</td></tr><tr><td>3056F3T</td><td>10</td><td>1 to 10,000</td><td>0.5 to 1.5</td><td>-67 to +325</td></tr><tr><td>3056F4T</td><td>20</td><td>1 to 10,000</td><td>0.5 to 1.5</td><td>-67 to +325</td></tr><tr><td>3056F5T</td><td>50</td><td>1 to 10,000</td><td>0.5 to 1.5</td><td>-67 to +325</td></tr><tr><td>3056F7T</td><td>200</td><td>1 to 10,000</td><td>0.5 to 1.5</td><td>-67 to +325</td></tr><tr><td>3056F8T</td><td>500</td><td>1 to 10,000</td><td>0.5 to 1.5</td><td>-67 to +325</td></tr></tbody></table>		Model	Sensitivity (mV/g)	Frequency Response, ±10% (Hz)	Time Constant (Sec)	Operating Temp (°F)	3056F2T	5	1 to 10,000	0.5 to 1.5	-67 to +325	3056F3T	10	1 to 10,000	0.5 to 1.5	-67 to +325	3056F4T	20	1 to 10,000	0.5 to 1.5	-67 to +325	3056F5T	50	1 to 10,000	0.5 to 1.5	-67 to +325	3056F7T	200	1 to 10,000	0.5 to 1.5	-67 to +325	3056F8T	500	1 to 10,000	0.5 to 1.5	-67 to +325
Model	Sensitivity (mV/g)	Frequency Response, ±10% (Hz)	Time Constant (Sec)	Operating Temp (°F)																																						
3056F2T	5	1 to 10,000	0.5 to 1.5	-67 to +325																																						
3056F3T	10	1 to 10,000	0.5 to 1.5	-67 to +325																																						
3056F4T	20	1 to 10,000	0.5 to 1.5	-67 to +325																																						
3056F5T	50	1 to 10,000	0.5 to 1.5	-67 to +325																																						
3056F7T	200	1 to 10,000	0.5 to 1.5	-67 to +325																																						
3056F8T	500	1 to 10,000	0.5 to 1.5	-67 to +325																																						
Refer to the performance specifications of the products in this family for detailed description																																										
PHYSICAL Weight Connector Mounting Provision Material, Housing/Connector Sensing Element Element Style		Type Tapped Hole																																								
PERFORMANCE Sensitivity, ±5% [2] Range for ± 5 Volts Output Frequency Response, ±5% Frequency Response, ±10% Resonant Frequency Broad Band Resolution Linearity [3] Maximum Transverse sensitivity Strain Sensitivity @ 250µε		<table><thead><tr><th>ENGLISH</th><th></th><th>SI</th><th></th></tr></thead><tbody><tr><td>0.35</td><td>oz</td><td>10.0</td><td>grams</td></tr><tr><td>10-32</td><td></td><td>10-32</td><td></td></tr><tr><td>10-32 X .150 ↓</td><td></td><td>10-32 X .150 ↓</td><td></td></tr><tr><td>Titanium</td><td></td><td>Titanium</td><td></td></tr><tr><td>Ceramic</td><td></td><td>Ceramic</td><td></td></tr><tr><td>Planar Shear</td><td></td><td>Planar Shear</td><td></td></tr></tbody></table>		ENGLISH		SI		0.35	oz	10.0	grams	10-32		10-32		10-32 X .150 ↓		10-32 X .150 ↓		Titanium		Titanium		Ceramic		Ceramic		Planar Shear		Planar Shear												
ENGLISH		SI																																								
0.35	oz	10.0	grams																																							
10-32		10-32																																								
10-32 X .150 ↓		10-32 X .150 ↓																																								
Titanium		Titanium																																								
Ceramic		Ceramic																																								
Planar Shear		Planar Shear																																								
		<table><tbody><tr><td>100</td><td>mV/g</td><td>10.20</td><td>mV/m/s²</td></tr><tr><td>50</td><td>g pk</td><td>490</td><td>m/s² pk</td></tr><tr><td>1 to 5,000</td><td>Hz</td><td>1 to 5,000</td><td>Hz</td></tr><tr><td>1 to 10,000</td><td>Hz</td><td>1 to 10,000</td><td>Hz</td></tr><tr><td>> 35</td><td>kHz</td><td>> 35</td><td>kHz</td></tr><tr><td>0.0003</td><td>g RMS</td><td>0.0029</td><td>m/s² RMS</td></tr><tr><td>± 1</td><td>% F.S.</td><td>± 1</td><td>% F.S.</td></tr><tr><td>5</td><td>%</td><td>5</td><td>%</td></tr><tr><td>0.002</td><td>g/µε</td><td>0.02</td><td>m/s²/µε</td></tr></tbody></table>		100	mV/g	10.20	mV/m/s ²	50	g pk	490	m/s ² pk	1 to 5,000	Hz	1 to 5,000	Hz	1 to 10,000	Hz	1 to 10,000	Hz	> 35	kHz	> 35	kHz	0.0003	g RMS	0.0029	m/s ² RMS	± 1	% F.S.	± 1	% F.S.	5	%	5	%	0.002	g/µε	0.02	m/s ² /µε			
100	mV/g	10.20	mV/m/s ²																																							
50	g pk	490	m/s ² pk																																							
1 to 5,000	Hz	1 to 5,000	Hz																																							
1 to 10,000	Hz	1 to 10,000	Hz																																							
> 35	kHz	> 35	kHz																																							
0.0003	g RMS	0.0029	m/s ² RMS																																							
± 1	% F.S.	± 1	% F.S.																																							
5	%	5	%																																							
0.002	g/µε	0.02	m/s ² /µε																																							
ENVIRONMENTAL Maximum Shock Temperature Range TEDS Operating Temperature Range Seal		<table><tbody><tr><td>1,000</td><td>g pk</td><td>9800</td><td>m/s² pk</td></tr><tr><td>-67 to +325</td><td>°F</td><td>-55 to +163</td><td>°C</td></tr><tr><td>-40 to +185</td><td>°F</td><td>-40 to +85</td><td>°C</td></tr><tr><td>Hermetic</td><td></td><td>Hermetic</td><td></td></tr></tbody></table>		1,000	g pk	9800	m/s ² pk	-67 to +325	°F	-55 to +163	°C	-40 to +185	°F	-40 to +85	°C	Hermetic		Hermetic																								
1,000	g pk	9800	m/s ² pk																																							
-67 to +325	°F	-55 to +163	°C																																							
-40 to +185	°F	-40 to +85	°C																																							
Hermetic		Hermetic																																								
ELECTRICAL Supply Current Range [4] Compliance Voltage Range Output Impedance, Typ Bias Voltage Discharge Time Constant TEDS Feature Electrical Isolation		<table><tbody><tr><td>2 to 20</td><td>mA</td><td>2 to 20</td><td>mA</td></tr><tr><td>+18 to +30</td><td>Volts</td><td>+18 to +30</td><td>Volts</td></tr><tr><td>100</td><td>Ω</td><td>100</td><td>Ω</td></tr><tr><td>+9 to +14</td><td>VDC</td><td>+9 to +14</td><td>VDC</td></tr><tr><td>0.5 to 1.5</td><td>Sec</td><td>0.5 to 1.5</td><td>Sec</td></tr><tr><td>IEEE 1451.4</td><td></td><td>IEEE 1451.4</td><td></td></tr><tr><td>10.0</td><td>GΩ, min</td><td>10.0</td><td>GΩ, min</td></tr></tbody></table>		2 to 20	mA	2 to 20	mA	+18 to +30	Volts	+18 to +30	Volts	100	Ω	100	Ω	+9 to +14	VDC	+9 to +14	VDC	0.5 to 1.5	Sec	0.5 to 1.5	Sec	IEEE 1451.4		IEEE 1451.4		10.0	GΩ, min	10.0	GΩ, min											
2 to 20	mA	2 to 20	mA																																							
+18 to +30	Volts	+18 to +30	Volts																																							
100	Ω	100	Ω																																							
+9 to +14	VDC	+9 to +14	VDC																																							
0.5 to 1.5	Sec	0.5 to 1.5	Sec																																							
IEEE 1451.4		IEEE 1451.4																																								
10.0	GΩ, min	10.0	GΩ, min																																							
		 																																								
																																										
		Units on the line drawing are in inches, units in brackets are in millimeters. Refer to 127-3056 for more information.																																								



21592 Marilla Street, Chatsworth, California 91311 Phone: 818.700.7818 Fax:818.698.0362 www.dytran.com

For permission to reprint this content, please contact info@dytran.com



21592 Marilla Street, Chatsworth, California 91311 Phone: 818.700.7818 Fax: 818.698.0362 www.dytran.com
 For permission to reprint this content, please contact info@dytran.com