

Adhesives

Model	Description
6273	mounting wax, 20 grams



6273

Tools

Model	Description
6239	vibration probe, 0.5" hex, 6" long, 10-32 tapped hole, aluminum
6591A	installation and removal wrench, aluminum, 3225E and 3225F series
6725A	installation and removal wrench, aluminum, 3224A series
6741	installation and removal wrench, aluminum, 3133A series



6239



6591A



6725A



6741

Adhesive Mounting Bases

Model	Hex Size (in)	Thickness (in)	Mounting Thread	Material
6167	0.375	0.125	2-56	stainless steel
6207	0.375	0.156	5-40	aluminum
6213	0.625	0.260	10-32	stainless steel
6221	0.625	0.180	10-32	aluminum
6228	0.500	0.200	10-32	aluminum



6213



6167



6207



6221



6228



6222



6223



6226



6243



6244



6245



6268



6714

Mounting Isolation Adapters

Model	Hex Size (in)	Thickness (in)	Mounting Thread	Material
6222	0.375	0.156	5-40	aluminum
6223	0.375	0.340	10-32	aluminum
6226	0.625	0.180	10-32	aluminum
6243	0.375	0.280	10-32	aluminum
6244	0.375	0.375	10-32	aluminum
6245	0.625	0.375	10-32	aluminum
6268	0.312	0.140	5-40	aluminum
6714	0.560	0.340	4-40	aluminum

Magnetic Mounting Bases

Model	Hex Size (in)	Thickness (in)	Mounting Thread	Material
6196	0.750	0.400	10-32	stainless steel
6199	0.375	0.210	2-56	stainless steel
6209	1.000	0.740	10-32	stainless steel
6258	0.625	0.390	10-32	stainless steel
6265	0.375	0.210	5-40	stainless steel
6272	0.625	0.430	10-32	stainless steel
6284	0.500	0.430	10-32	stainless steel
6295	0.250	0.120	flat surface for adhesive mount	stainless steel
6729	0.625	0.505	4-40	stainless steel



6196



6199



6209



6258



6265



6272



6284



6295



6729



6166



6176



6200



6200S



6201



6203



6205



6580

Studs

Model	Threads			Material
6166	10-32	to	2-56	stainless steel
6176	1/4-28	to	1/4-28	stainless steel
6200	10-32	to	10-32	copper alloy
6200S	10-32	to	10-32	stainless steel
6201	10-32	to	1/4-28	copper alloy
6203	10-32	to	M6 x 1.0	copper alloy
6205	5-40	to	10-32	copper alloy
6580	5-40	to	5-40	copper alloy

Triaxial Mounting Blocks

Model	Dimensions (in)	Mounting	Material
6159	0.38 cube	flat surface for adhesive mount	stainless steel
6240A	1 cube	10-32	aluminum
6240S	1 cube	10-32	stainless steel
6241	0.75 cube	10-32	aluminum
6269	0.38 cube	5-40	aluminum
6552	2.5 cube	1/4-28	aluminum
6717	1.2 cube	4-40	aluminum



6159



6240A



6240S



6241



6269



6552



6717



6164



6165



6238A1



6238A2



6247A2



6297



6523



6524



6535



6545A1



6722



6746



6914

Mounting Screws

Model	Thread	Length (in)	Material
6164	6-32	0.75	stainless steel
6165	2-56	0.38	aluminum
6238A1	8-32	0.65	stainless steel
6238A2	8-32	0.75	stainless steel
6247A2	6-32	0.40	stainless steel
6297	6-32	0.54	stainless steel
6523	1/4-28	1.07	stainless steel
6524	1/4-28	0.89	stainless steel
6535	8-32	0.50	stainless steel
6545A1	4-40	0.31	stainless steel
6722	M2	0.47	stainless steel
6746	4-40	0.31	stainless steel
6914	M2	0.79	stainless steel

Immersion Proof™ and Protective Boots

Model	Hex (in)	Length (in)	Material
6185	0.9	3.4	Viton™
6194	1.1	2.67	Viton™
6529	0.94	3.87	Viton™



6185



6194



6529