



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF DYTRAN INSTRUMENTS INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF DYTRAN INSTRUMENTS, INC. IS PROHIBITED



REVISIONS

REV.	ECN	DESCRIPTION	BY/DATE	CHK	APPR
C	5057	IS:1/4-28 UNF-2A FOR 3086A1 THRU A6 10-32 UNF-2A FOR 3086A1T THRU A6T WAS: 1/4-28 UNF-2A	RA, 2/13/08	JS	JS
D	5498	ADDED WIRES & O RING	JS 10/16/08	AS	DV
E	12854	ADDED WIRE LENGTH DIMENSION	NDC 07/28/16	LN	RT
F	16156	UPDATED RENDERING	KG 04/26/21	RA	LN



2. HOUSING MATERIAL: TITANIUM ALLOY




1. RECOMMENDED MOUNTING TORQUE:
30 LB-IN

DRILL HOLE SIZE		TOLERENCE		UNLESS OTHERWISE SPECIFIED: INTERPRET DIM & TOL PER ASME Y14.5M - 1994. REMOVE BURRS. COUNTERSINK INTERNAL THDS 90° TO MAJOR DIA. CHAM EXT THDS 45° TO MINOR DIA. THD LENGTHS AND DEPTHS ARE FOR MIN FULL THDS. THDS PER MIL-S-7742. DIMENSIONS APPLY AFTER FINISHING. ALL MACHINED SURFACES. TOTAL RUNOUT WITHIN .005. BREAK SHARP EDGES .005 TO .010. MACHINED FILLET RADII .005 TO .015. WELDING SYMBOLS PER AWS A2.4. ABBREVIATIONS PER MIL-STD-12.		UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES. TOLERANCES ARE: DECIMALS .XX ± .010 .XXX±.005 ANGLES ± 1°		DYTRAN INSTRUMENTS, INC. Chatsworth, CA		TITLE: OUTLINE DRAWING, 3086A			
MATERIAL		APPROVALS											
FINISH		ORIG								PML		3/28/07	
DO NOT SCALE DRAWING		CHK								JS		2/15/08	
		APP								DV		10/17/08	
APP													

SIZE	CAGE CODE	DWG. NO.	REV
A	2W033	127-3086A	F

SCALE: 4:1	SOLIDWORKS	SHEET 1 OF 1
------------	------------	--------------

THIRD ANGLE PROJECTION USA 	
-----------------------------------	--

Model Number 3086A5T		PERFORMANCE SPECIFICATION				DOC NO PS3086A5T	
		MINIATURE IEPE ACCELEROMETER				REV D, ECN 16156, 04/27/21	
		• MINIATURE SIZE • HERMETICALLY SEALED					
		ENGLISH		SI			
PHYSICAL							
Weight		0.12	oz	3.5	grams		
Connector	Top Mounted	Solder Pins		Solder Pins			
Mounting Provision	Integral Stud	10-32 UNF-2A		10-32 UNF-2A			
Material	Accelerometer and Connector	Titanium Alloy		Titanium Alloy			
Element Style		Quartz Compression		Quartz Compression			
PERFORMANCE							
Sensitivity, Nom. [1]		1.00	mV/g	0.10	mV/m/s ²		
Range Full Scale		±5000	g pk	±49000	m/s ² pk		
Low Frequency -3dB Point, Nom		0.16	Hz	0.16	Hz		
Low Frequency -5% Point		0.5	Hz	0.5	Hz		
Frequency Response, ±10%		0.35 to 10000	Hz	0.35 to 10000	Hz		
Resonant Frequency		>100	kHz	>100	kHz		
Isolation Cup Resonance		>45	kHz	>45	kHz		
Electrical Noise		0.07	g RMS	0.69	m/s ² RMS		
Linearity [2]		±1	% F.S.	±1	% F.S.		
Maximum Transverse Sensitivity		3	%	3	%		
ENVIRONMENTAL							
Maximum Shock		±50000	g pk	±490000	m/s ² pk		
Temperature Range		-60 to +250	°F	-51 to +121	°C		
Environmental Seal		Hermetic		Hermetic			
ELECTRICAL							
Supply Current Range [3]		2 to 20	mA	2 to 20	mA		
Compliance Voltage Range [3]		+18 to +30	Volts	+18 to +30	Volts		
Output Impedance, Nom		100	Ω	100	Ω		
Bias Voltage		+7.5 to +9.5	VDC	+7.5 to +9.5	VDC		
Discharge Time Constant		0.8 to 2.0	Sec	0.8 to 2.0	Sec		
Ground Isolation, Case to Mounting Surface, Min		10	MΩ	10	MΩ		
		This family also includes:					
		Model	Sensitivity (mV/g)	Range F.S. (g pk)	Maximum Shock (g pk)	Operating Temp (°F)	
		3086A1T	0.05	70,000	100,000	-60 to +250	
		3086A2T	0.1	50,000	100,000	-60 to +250	
		3086A3T	0.25	20,000	100,000	-60 to +250	
		3086A4T	0.5	10,000	50,000	-60 to +250	
		3086A6T	2.0	2,500	50,000	-60 to +250	
		Please refer to the performance specifications of the products in this family for detailed description					
		Supplied Accessories:					
		1) Accredited calibration certificate (ISO 17025)					
		Notes:					
		[1] Measured by impacting against calibrated force sensor. NIST traceable.					
		[2] Percent of full scale or any lessor full scale range, zero-based best fit straight line method.					
		[3] Power only with Dytran or Dytran approved current source type power unit. Do not supply power without current limiting. To do so will destroy the integral electronics. This will void the warranty.					
		[4] Recommended Cable: Dytran Part No. 128-6869AXX (XX denotes length in feet)					
		[5] In the interest of constant product improvement, we reserve the right to change specifications without notice.					
		It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.					
		[6] All specifications are at room temperature unless otherwise specified.					
		TYPICAL LOW FREQUENCY RESPONSE  TYPICAL TEMPERATURE RESPONSE  					
		Units on the line drawing are in inches. Refer to 127-3086A for more information.					



21592 Marilla Street, Chatsworth, California 91311 Phone: 818.700.7818 Fax:818.698.0362 www.dytran.com
For permission to reprint this content, please contact info@dytran.com



21592 Marilla Street, Chatsworth, California 91311 Phone: 818.700.7818 Fax: 818.698.0362 www.dytran.com
 For permission to reprint this content, please contact info@dytran.com