

Terms and Conditions of Use

This drawing, including all information depicted herein (collectively, "Drawing"), is FUTEK's property and protected under applicable law, including copyright. FUTEK reserves all rights. The Drawing is provided solely for your information and exclusive use. **Except as expressly approved by FUTEK in writing, you may not reproduce or share this Drawing**, in whole or part, with any other firm or individual, or attempt to reverse engineer the Drawing or data contained therein. Any reproduction of this Drawing in whole or part must include this legend.

By accessing the Drawing, you agree that you have read, understand, and agree to abide by the stated Terms and Conditions of Use.

© 2023 FUTEK Advanced Sensor Technology, Inc.

FUTEK MODEL QLA292 Custom Donut Load Cell (SKF)

STOCK NUMBER: QSH01203

SUPERSEDES QSH01024-A $\triangle$

INCH [mm] | R.O.= Rated Output

WIRING CODE

+Excitation	-Excitation	+Signal	-Signal
RED	BLACK	GREEN	WHITE
Shield			
Floating			

6x M4x0.7 X 0.38
[9.65] DEEP
EQUALLY SPACED ON
5.625 [142.88] B.C.D.
(FAR SIDE)

$\triangle$

6x M4x0.7 X 0.38
[9.65] DEEP
EQUALLY SPACED ON
4.250 [107.95] B.C.D.

$\triangle$

NONLOADING
SURFACE

$\varnothing 5.25$ [$\varnothing 133.35$]


$\varnothing 4.65$ [$\varnothing 118.11$]

$\varnothing 3.25$ [$\varnothing 82.55$] $\triangle$

$\varnothing 3.9370^{+0.0025}_{-0.0005}$ [$100.00^{+0.06}_{-0.01}$] $\triangle$

+OUTPUT
(COMPRESSION)

LOADING
SURFACE



SPECIFICATIONS:

RATED OUTPUT	1.5 mV/V nom.
CAPACITY	25000 lbs
SAFE OVERLOAD	150% of R.O.
ZERO BALANCE	±3% of R.O.
EXCITATION (VDC OR VAC)	18 MAX
BRIDGE RESISTANCE	700 Ω nom
NONLINEARITY	±2% of R.O.
HYSTERESIS	±2% of R.O.
NONREPEATABILITY	±0.5% of R.O.
TEMP. SHIFT ZERO	±0.02% of R.O./°F (0.036% of R.O./°C)
TEMP. SHIFT SPAN	±0.02% of LOAD/°F (0.036 of LOAD/°C)
COMPENSATED TEMP.	-26 to 126°F (-32 to 52°C)
OPERATING TEMP.	-40 to 185°F (-40 to 85°C)
WEIGHT	approx 7.5 lb
MATERIAL	17-4ph S.S.
CABLE: 24 AWG, 4 Conductor Braided Shielded Teflon Cable, 5 ft [1.5m] long	

MATERIAL:

—

HEAT TREATMENT - FINISH:

—

REVISIONS: (Refer to dwg # revision sheet)

- $\triangle$ 11-21-07
- $\triangle$ 12-03-07
- $\triangle$ 12-10-07
- $\triangle$ 09-08-08
- $\triangle$ 02-17-09

OUTLINE DRAWING

STANDARD NOTES: (Unless Otherwise Specified)

- ALL DIMENSIONS ARE IN INCHES
- DRAWING INTERPRETATION DIMS. PER ASME-Y14.5M
- REMOVE BURRS AND BREAK SHARP EDGES .005 - .015
- THREADS PER HANDBOOK H-28
- DIMENSIONS ARE SHOWN AFTER PLATING

ANGLE:
±1/2°

CHAMFER:
±5°

TOLERANCE:
.X ±0.1
.XX ±0.01
.XXX ±0.005

3rd ANGLE PROJ.



FUTEK

This drawing, including all information depicted herein (collectively, "Drawing"), is FUTEK's property and protected under applicable law, including copyright. FUTEK reserves all rights. The Drawing is provided solely for your information and exclusive use. **Except as expressly approved by FUTEK in writing, you may not reproduce or share this Drawing**, in whole or part, with any other firm or individual, or attempt to reverse engineer the Drawing or data contained therein. Any reproduction of this Drawing in whole or part must include this legend.

CAGE: 1X8M6

MODEL: QLA292

DRAWN BY: R. WALKER

APPROVED BY: —

DWG No.: F01193-E

CHECKED BY: J. VARGAS

DATE: Nov 1, 2007